


# MINI HD265 WiFi

Full HD Digital HEVC Satellite Receiver with Over-The Top Content with card reader



audio and video codecs are subjects to availability\*



## MAIN FEATURES

- One Conax embedded smart card reader
- HEVC decoding support
- 6000 channels (TV and Radio) programmable
- One High Speed USB 2.0 Connections
- Ethernet Connection & USB WiFi Support (Ralink RT5370 chip only)
- RSS Reader & Weather Forecast Function
- Channel Recording to External Storage Devices (optional)
- Timeshift support
- Channel Recording & Timeshifting Simultaneously (optional)
- Channel switching time less than 1 second
- True-color, User Friendly On-Screen Display (OSD)
- Full Picture In Graphic (PIG) function
- Electronic Program Guide (EPG)
- Subtitle supported
- Parental lock facility by channel and program event
- Program and Channel information transfer from receiver to receiver
- Satellite Blind Scan & Fast Scan support
- DiSEqC 1.0, 1.1, 1.2 and USALS Compatible
- Full HD (1080p) Output via Digital Video Output
- Exciting games embedded
- Multi-Language support
- Software upgrade support via USB, Network, OTA, RS232
- Power Consumption in Stand-By: <0.5W

\*Features and specifications are subject to change without notice. All Pictures shown are for illustration purpose only.

# MINI HD265 WiFi



## TECHNICAL SPECIFICATIONS

### Tuner & Demodulation

<b>Tuner Type:</b>	<b>DVB-S / DVB-S2</b>
Input Connector:	F-type, Connector, Female
Signal Level:	-65 to -25 dBm
LNB Power & Polarization:	Vertical: +13V/+14V, Horizontal: +18V/+19V Max. 400mA (Overload Protection)
Current:	22±1KHz
22KHz Tone Frequency:	Version 1.0, 1.1, 1.2, USALS
DiSEqC Control:	QPSK, 8PSK
Demodulation:	2-45 Mbps,
Input Symbol Rate:	1/2, 2/3, 3/4, 5/6, 7/8 and Auto
FEC:	

### MPEG TS A/V Decoding

Transport Stream:	MPEG-2, H.264, H.265
Input Rate:	Max.120Mbit/s
Aspect Ratio:	4:3, 16:9, Letter Box
Video Decoding:	MPEG-4/H.265 SP@L3 to ASP@L5, AVC, HP@level 4.1, MP@level 4.1
Video Resolution:	720*480P/I, 720*576P/I, 1280*720p, 1920*1080i, 1920*1080p
Audio Decoding:	MPEG-1/2,AAC-LC,HE-AAC,MP3,Dolby Digital
Audio Mode:	Left / Right / Stereo/ Mono
Sampling Rate:	32, 44.1 and 48KHz

### System Resources

Main Processor:	800MHz CPU
Flash Memory:	16MB
DDR3 RAM:	256MB

### Power Supply

Input Voltage:	12V DC
Power Consumption:	24W Max
Stand-By Power Consumption:	<0.5W

### A/V & Data Input/Output

RCA:	CVBS Video out, L&R Audio out
RS-232C:	Jack-type, Transfer rate 115.2Kbps, 9 pin D-sub Type
USB:	One USB 2.0 slots
S/PDIF:	Coaxial
Digital Video Output:	VER1.4, Type A
Ethernet:	10/100M RJ45
IR IN:	Jack-type, External IR sensor connection

### Physical Specifications

Size[W*H*D]:	144mm x 40mm x 110mm
Net Weight:	0.5KG
Operation Temperature:	0°C~+45°C
Storage Temperature:	-10°C~+70°C
Storage Humidity:	5%~95% RH (Non-Condensing)

\*Features and specifications are subject to change without notice. All Pictures shown are for illustration purpose only.